

Improved driver safety and accident prevention

Product overview

FleetUp Al Dashcams provide fleet managers with unprecedented visibility into what is happening on the road and inside the cab.

FleetUp AI Dashcams include both forward-facing cameras that record hazardous road events (e.g. collision warning, reduce speed) and driver-facing cameras that monitor unsafe driving behaviors (e.g. falling asleep, distracted driving, talking, texting on a cell phone).



FleetUp Al Dashscam

All recorded video events are stored on the Al Dashcam local memory card and later uploaded to the FleetUp cloud for further examination and analysis.

The ability of the Al Dashcam to monitor vehicles and drivers remotely puts fleet managers "in the driver's seat" enabling them to see exactly what the driver sees and provide real-time driver coaching.

Key features

- Al technology
- Dual-facing HD cameras
- · Infrared LEDs
- · Voice assistant driver alerts
- Automatic uploads of event footage
- · On-demand video retrieval
- · Cloud-based video storage
- · Event and accident replay
- FleetUp web app support

Key benefits

- Event-specific video recordings
- · Reduced accident risk
- Night time video recording
- · Improved driver safety and training
- Videos can be stored for further review
- Driver exoneration
- · Video content stored for 6 months
- Lower insurance premiums
- · Remote management from anywhere



Trucks, vans, commercial and passenger vehicles





FleetUp Al Dashcams provide an early warning system that ensures the highest level of driver safety

Specifications

Front-facing camera	 Field of view: H=118° / D=145° Resolution: 1920 x 1080 Frame rate: 25FPS
Driver-facing camera	 Field of view: H=90° / D=140° Resolution 1280 x 720 Frame rate: 15FPS Night vision, black and white for better DMS performance
Audio speaker	Speaker: To notify drivers of status or events
Storage	About 34 hour @ 128GB (Hours of 1080p footage)

Connectivity	3G / 4G
SD capacity	128GB
Dimensions	109 x 69 x 52 mm
Mounting	Inside front windshield
Power	DC 9V-30V
Battery	450mAh
Operating temp	-4°F to 158°F -20°C to 70°C
Automatic upload	Supported
On-demand upload	Supported

Increase your operational visibility today.

For more information, please visit <u>www.fleetup.com</u>